



ANACO FAMILY OF COUPLINGS



Anaco is the largest manufacturer of couplings in the United States providing the perfect solution for joining hub-less cast iron pipe and fittings in drainage, waste and vent (DWV) plumbing systems as well as dissimilar piping products—a **complete coupling solution**.

PRODUCTS

- Anaco No-Hub Coupling
- Cremco Transition Coupling
 - Shielded Transition Coupling
 - ARC Shielded Coupling
- Rigid Quik Coupling
- Service Weight Gaskets
- Husky CR 7000 Coupling
 - 316-SS Corrosion Resistance
- Husky SD 4000 Coupling
- Husky HD 2000 Coupling
- Husky Transition Coupling
 - SD 4200-PVC x Cast Iron
 - SD 4100-Copper x Cast Iron
 - SD 4000- Cast Iron Reducers



HUSKY SD 4000 COUPLINGS

Husky SD 4000 Couplings have been engineered by Anaco to provide a heavy-duty, all stainless steel coupling, balancing the desire for a more rigid joint with the need to provide a superior positive seal, which can accommodate possible disparities in the No-Hub pipe and fittings. This has been accomplished by manufacturing our coupling with a super-duty corrugated shield of sufficient width to accommodate additional surface-bearing sealing clamps.

Size	Width	# Straps	Torque
1 1/2" to 4"	3.0	4	80
5" & 6"	4.0	6	80
8" & 10"	4.0	6	80
12" & 15"	5.5	6	80

PRODUCTS

- Husky SD 4000
- Husky SD 4200 Transition
 - PVC x CI 1 1/2"—10"
- Husky SD 4000 Reducer
 - 2"x 1 1/2", 3"x 2", 4"x 3", 4"x 2"
- Husky SD 4100 Transition
 - CI x Copper 2"x 1 1/2", 2"x 2"

CERTIFICATIONS & STANDARDS

Tested & Certified to:

- ASTM C 1540
 - 4200 Meets ASTM C 1460
- ASTM C 564
- FM 1680 Class 1
- CSA B 602
- IAPMO File 6726
 - 4200 IAPMO File 5794

APPLICATIONS

- Hospitals
- Storm Systems
- Correctional
- Airports
- Universities
- Seismic Areas
- Data Centers/Labs
- Convention Centers
- Museums
- Government
- Sports Stadiums
- High Rises



HUSKY CR 7000 316 STAINLESS STEEL

The Husky CR 7000 Corrosion Resistant Coupling is the first 316 stainless steel, heavy-duty coupling. It balances the desire for a more rigid joint with the need to provide a superior positive seal, which can accommodate possible disparities in the no-hub pipe & fittings. Sizes 1½"–10"

APPLICATIONS

- Corrosive Environments
- Around Waterways
- Exposed Areas
- Parking Garages
- Bridges/Tunnels
- Underground



CERTIFICATIONS & STANDARDS

Tested & Certified to:

- ASTM C 1540
- ASTM C 564
- CSA B 602
- IAPMO File 6726



HUSKY HD 2000 COUPLINGS

The Husky HD 2000 Couplings have a slightly thinner shield than the Husky SD 4000. They consist of a 304 stainless steel shield, clamp assembly and a neoprene gasket. The 305 stainless steel 5/16" screw requires 80-inch pounds of torque. Sizes 1½"–10"

APPLICATIONS

- Hotels
- Industrial
- Commercial
- Casinos
- Municipal
- Offices



CERTIFICATIONS & STANDARDS

Tested & Certified to:

- ASTM C 1540
- ASTM C 564
- FM 1680 Class 1
- CSA B 602
- IAPMO File 6726



anaco STANDARD NO-HUB COUPLING

CERTIFICATIONS & STANDARDS

Tested & Certified to:

- CISPI 310
- ASTM C 1277
- ASTM C 564
- NSF™ Certified
- IAPMO File 2206

Anaco No-Hub couplings consist of a 300 Series stainless steel shield, clamp assembly and a Neoprene gasket. Coupling sizes range from 1½" through 15" diameters.



CREMCO TRANSITION COUPLING

Couplings by Anaco

PRODUCTS

- **Cremco Specialty Transition Coupling**
 - Shielded Transition Coupling
 - ARC Shielded Coupling
- **Rigid Quik Unshielded Couplings**
 - Meets ASTM 1461

FEATURES

- Meets and exceeds material and performance requirements of ASTM C 1460
- Neoprene gaskets meet and exceed ASTM C 564
- Neoprene gaskets integrate transitional design with center stop serving as noise dampening mechanism
- All 300-series stainless steel components meet ASTM A 240



SERVICE WEIGHT GASKETS

PRODUCTS

- Ty-Seal
- EZ-Tight

FEATURES

- Available in sizes from 2"—15"
- Neoprene rubber meets/exceeds ASTM C 564